

## Rubber-Steel-Gaskets



### Summary

- Rubber-Steel-Gasket with vulcanized steel ring for perfect sealing and safe centering according to DIN EN 1514-1 (PN 6 – PN 40)
- Generally used for pipeline construction (gas, water, sewage, oil, chemicals), for enamelled and coated pipes and for plastic pipes.
- Perfect sealing of water, gas, air, dilute acid and base and aliphatic hydrocarbon.
- Material:  
EPDM with tap water certification according to KTW D1/D2, 1.3.13 of BGA f. Trinkwasser and DVGW-W270  
*or*  
NBR with gas certification according to DVGW EN 682
- For dimensions from DN 15 up to DN 2000

## Dimensions Rubber-Steel-Gaskets

DN	Quality NBR					Quality EPDM				
	Gas certification according to DVGW EN 682					Tap water certification according to DVGW-W270				
	PN 6	PN 10	PN 16	PN 25	PN 40	PN 6	PN 10	PN16	PN25	PN40
15	o	x	x	x	x	o	x	x	x	x
20	o	x	x	x	x	o	x	x	x	x
25	o	x	x	x	x	o	x	x	x	x
32	x	x	x	x	x	x	x	x	x	x
40	o	x	x	x	x	x	x	x	x	x
50	x	x	x	x	x	x	x	x	x	x
65	x	x	x	x	x	x	x	x	x	x
80	o	x	x	x	x	x	x	x	x	x
100	x	x	x	x	x	x	x	x	x	x
125	x	x	x	x	x	x	x	x	x	x
150	x	x	x	x	x	x	x	x	x	x
200	x	x	x	x	x	x	x	x	x	x
250	x	x	x	x	x	x	x	x	x	x
300	x	x	x	x	x	x	x	x	x	x
350	x	x	x	x	x	x	x	x	x	x
400	x	x	x	x	x	x	x	x	x	x
450	x	x	x	x	x	x	x	x	x	x
500	x	x	x	x	o	x	x	x	x	o
600	x	x	x	x	x	x	x	x	x	x
700	x	x	x	x	o	x	x	x	x	o
800	x	x	x	x	o	x	x	x	x	o
900	x	x	x	x	o	x	x	x	x	o
1000	x	x	x	x	o	x	x	x	x	o
1100	o	o	x	x	o	o	o	x	x	o
1200	x	x	x	x	o	x	x	x	x	o
1400	o	x	o	o	o	o	x	o	o	o
1600	o	x	o	o	o	o	x	o	o	o
1800	o	x	o	o	o	o	x	o	o	o
2000	o	x	o	o	o	o	x	o	o	o

x = available

o = not available